



TYREX WINCH 12000 LB

Line Speed / AMP Draw (First Layer)							
Line	lbs	No	4000	6000	8000	10000	12000
Pull	kg	Load	1814	2722	3629	4536	5443
Line Speed	ft/min	22	12.5	9.8	7.6	6.9	5.6
	m/min	6.8	3.8	3.0	2.3	2.1	1.7
Motor	Amps 12V	80	170	210	250	310	360

Rated Line Pull	12000lbs(5443kgs)
Winch Motor	Series wound 6.0hp/4.4kw 12V
Control	Remote Control
Gear Train	3-Stage Planetary
Gear Reduction Ratio	265:1
Clutch	Sliding Ring Gear
Brake Action	Automatic in drum
Drum Diameter	64mm
Drum Length	226mm
Steel Cable	Dia 9.5mmx26m
Fairlead	4-Way Roller Fairlead
Remote Control	Included
Battery	650CCA min. for winching
Battery Leads	25mm ² x1.8m
Dimensions	548mm l.x160mm d.x218mm h.
Mounting Bolt Pattern	254mm x 114.3mm
Weight	93lbs(42kgs)

12000 lbs Line Pull and Cable Capacity					
Layers of Cable		1	2	3	4
Rated Line Pull Per Layer	lbs	12000	9900	8300	7000
	kg	5443	4490	3765	3175
Cable Capacity Per Layer	ft	17.6	37	63	85
	m	6.0	13	22	26